




Fastener Catalog




[AN3 thru AN6 - Steel, CRES or Aluminum \(Bolt - Machine, Aircraft, Hexagon Head\)](#)




[ANSI B18.1 - Steel \(Grade 8 Screws\)](#)




[MS51957 Revision D - 316 CRES only \(Pan Head, Cross-Recessed, Machine Screw\)](#)



[MS51959 Revision D - 316 CRES only \(Flat Countersunk Head, 82 Degree, Cross-Recessed, Machine Screw\)](#)



[MS16995 Revision H 316 CRES only \(Hexagon Socket Head, Cap Screw\)](#)



[MS35307 Revision E 316 CRES only \(Finished Hexagon Head, Cap Screw\)](#)

For additional assistance please contact: AVN Testing Office PVT Workflow AVNTestingOfficePVTWorkflow@dla.mil

Fastener Catalog - Table of Contents

Screws (5305) AN3 through AN6 Specifications

This Technical Reference Catalog provides Part Numbers and Dimensional Characteristics of 1,017 National Stock Numbers (NSNs) managed and supplied by DLA Troop Support Industrial Hardware. Each page provides a brief description of the Part and its assigned National Item Identification Number (NIIN). Below are the various Thread sizes available, as well as fastener Definitions/Terminology.

PLEASE NOTE: All referenced dimensions are in inches.

- [AN3](#) - 10-32 UNF-3A Threads
- [AN4](#) - 1/4-28 UNF-3A Threads
- [AN5](#) - 5/16-24 UNF-3A Threads
- [AN6](#) - 3/8-24 UNF-3A Threads

DEFINITIONS/TERMINOLOGY

These definitions are provided for general informational purposes only and do not constitute an official definition. Refer to the Specification and Standards referenced by each item description to determine manufacturing and performance standards.

STEEL, CADMIUM PLATED:

Bolts have good galvanic protection and excellent lubricity.

CORROSION RESISTANT STEEL, PASSIVATED:

Bolts have a high degree of corrosion resistance compared to carbon and alloy steels.

ALUMINUM ALLOY, ANODIZED:

Bolts have good galvanic protection and excellent lubricity.

FASTENER LENGTH:

The length from under the washer head to the bottom of the bolt.

GRIP LENGTH:

The length from under the washer head to the top of the threads.

HEAD WIDTH:

The distance across the flats.

HEAD HEIGHT:

The distance from the top of the bolt to the bottom of the washer face.

For additional assistance please contact: AVN Testing Office PVT Workflow AVNTestingOfficePVTWorkflow@dla.mil

**Specification AN3 Hexagon Head
Head Width 0.375 Inch
Head Height 0.125 Inch
10-32 UNF-3A Threads**

- [Steel, Cadmium Plated, Drilled Shank - 125,000 psi Tensile Strength](#)
 - [Steel, Cadmium Plated, Undrilled - 125,000 psi Tensile Strength](#)
 - [Steel, Cadmium Plated, Drilled Head and Shank - 125,000 psi Tensile Strength](#)
 - [Steel, Cadmium Plated, Drilled Head - 125,000 psi Tensile Strength](#)
 - [Corrosion-Resistant Steel, Passivated, Drilled Shank - 125,000 psi Tensile Strength](#)
 - [Corrosion-Resistant Steel, Passivated, Undrilled - 125,000 psi Tensile Strength](#)
 - [Corrosion-Resistant Steel, Passivated, Drilled Head and Shank - 125,000 psi Tensile Strength](#)
 - [Corrosion-Resistant Steel, Passivated, Drilled Head - 125,000 psi Tensile Strength](#)
 - [Aluminum Alloy, Anodized, Drilled Shank - 62,000 psi Tensile Strength](#)
 - [Aluminum Alloy, Anodized, Undrilled - 62,000 psi Tensile Strength](#)
 - [Aluminum Alloy, Anodized, Drilled Head and Shank - 62,000 psi Tensile Strength](#)
 - [Aluminum Alloy, Anodized, Drilled Head - 62,000 psi Tensile Strength](#)
-

**Steel, Cadmium Plated, Drilled Shank
125,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001513015	0.469	0.062	AN3-3
001443646	0.531	0.125	AN3-4
007150566	0.656	0.250	AN3-5
006806779	0.781	0.375	AN3-6
001443648	0.906	0.500	AN3-7
001443649	1.031	0.625	AN3-10
001443650	1.156	0.750	AN3-11
006852636	1.281	0.875	AN3-12
006852634	1.406	1.000	AN3-13
001443653	1.531	1.125	AN3-14
001443654	1.656	1.250	AN3-15
001443655	1.781	1.375	AN3-16
001443656	1.906	1.500	AN3-17
001443657	2.031	1.625	AN3-20
001443658	2.156	1.750	AN3-21
001443659	2.281	1.875	AN3-22
001443660	2.406	2.000	AN3-23
001443661	2.531	2.125	AN3-24
001443662	2.656	2.250	AN3-25
001443663	2.781	2.375	AN3-26
001443664	2.906	2.500	AN3-27
001443665	3.031	2.625	AN3-30
001443666	3.156	2.750	AN3-31
001443667	3.281	2.875	AN3-32
001443668	3.406	3.000	AN3-33
001443669	3.531	3.125	AN3-34
001443670	3.656	3.250	AN3-35
001443671	3.781	3.375	AN3-36
001443672	3.906	3.500	AN3-37
001443673	4.031	3.625	AN3-40
001443674	4.156	3.750	AN3-41
001443675	4.281	3.875	AN3-42

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001443676	4.406	4.000	AN3-43
001443677	4.531	4.125	AN3-44
001443678	4.656	4.250	AN3-45
001443679	4.781	4.375	AN3-46
001443680	4.906	4.500	AN3-47
001443681	5.031	4.625	AN3-50
001443682	5.156	4.750	AN3-51
001443683	5.281	4.875	AN3-52
001443684	5.406	5.000	AN3-53
001443685	5.531	5.125	AN3-54
001443686	5.656	5.250	AN3-55
001443687	5.781	5.375	AN3-56
001443688	5.906	5.500	AN3-57
001443689	6.031	5.625	AN3-60
001443691	6.281	5.875	AN3-62
001443692	6.406	6.000	AN3-63
001443693	6.531	6.125	AN3-64
001443697	7.031	6.625	AN3-70
001443699	7.406	7.000	AN3-73
001443700	7.531	7.125	AN3-74
001443701	7.781	7.375	AN3-76
001443702	8.031	7.625	AN3-80

Steel, Cadmium Plated, Undrilled
125,000 psi Tensile Strength

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001509221	0.469	0.062	AN3-3A
007220393	0.531	0.125	AN3-4A
002742119	0.656	0.250	AN3-5A
006560358	0.781	0.375	AN3-6A
001510785	0.906	0.500	AN3-7A
001510784	1.031	0.625	AN3-10A
006853027	1.156	0.750	AN3-11A
001510782	1.281	0.875	AN3-12A
001510781	1.406	1.000	AN3-13A
001510780	1.531	1.125	AN3-14A
001510779	1.656	1.250	AN3-15A
001510778	1.781	1.375	AN3-16A
001510777	1.906	1.500	AN3-17A
001510776	2.031	1.625	AN3-20A
001510775	2.156	1.750	AN3-21A
003372861	2.281	1.875	AN3-22A
001801948	2.406	2.000	AN3-23A
001509881	2.531	2.125	AN3-24A
001509874	2.656	2.250	AN3-25A
001509875	2.781	2.375	AN3-26A
001509876	2.906	2.500	AN3-27A
007251908	3.031	2.625	AN3-30A
001509878	3.156	2.750	AN3-31A
001509879	3.281	2.875	AN3-32A
001509880	3.406	3.000	AN3-33A
006162948	3.531	3.125	AN3-34A
001512153	3.656	3.250	AN3-35A
001512156	3.781	3.375	AN3-36A
001457701	3.906	3.500	AN3-37A
001512152	4.031	3.625	AN3-40A
001512151	4.156	3.750	AN3-41A

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001457720	4.281	3.875	AN3-42A
001457719	4.406	4.000	AN3-43A
001457718	4.531	4.125	AN3-44A
001457717	4.656	4.250	AN3-45A
001457716	4.781	4.375	AN3-46A
001457715	4.906	4.500	AN3-47A
001457714	5.031	4.625	AN3-50A
001457713	5.156	4.750	AN3-51A
001457712	5.281	4.875	AN3-52A
001457711	5.406	5.000	AN3-53A
001457710	5.531	5.125	AN3-54A
001457709	5.656	5.250	AN3-55A
001457708	5.781	5.375	AN3-56A
001457699	5.906	5.500	AN3-57A
001457707	6.031	5.625	AN3-60A
001457706	6.156	5.750	AN3-61A
001457700	6.281	5.875	AN3-62A
005829735	6.406	6.000	AN3-63A
001457705	6.656	6.250	AN3-65A
001457662	6.781	6.375	AN3-66A
001457704	6.906	6.500	AN3-67A
001457703	7.031	6.625	AN3-70A
005826690	7.156	6.750	AN3-71A
001457702	7.281	6.875	AN3-72A
005826691	7.406	7.000	AN3-73A
001511429	7.781	7.375	AN3-76A
002818933	7.906	7.500	AN3-77A
001511428	8.031	7.625	AN3-80A

**Steel, Cadmium Plated, Drilled Head and Shank
125,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
002824311	0.469	0.062	AN3H3
002824312	0.531	0.125	AN3H4
002824309	0.656	0.250	AN3H5
002824310	0.781	0.375	AN3H6
001802695	0.906	0.500	AN3H7
001802696	1.031	0.625	AN3H10
001821898	1.156	0.750	AN3H12
001821900	1.406	1.000	AN3H13
001821915	1.531	1.125	AN3H14
001821916	1.656	1.250	AN3H15
001821917	1.781	1.375	AN3H16
001821918	1.906	1.500	AN3H17
001821919	2.031	1.625	AN3H20
001821920	2.156	1.750	AN3H21
001821921	2.281	1.875	AN3H22
001821922	2.406	2.000	AN3H23
001821923	2.531	2.125	AN3H24
002089038	2.781	2.375	AN3H26
005826685	2.906	2.500	AN3H27
005791945	3.031	2.625	AN3H30
006392417	3.281	2.875	AN3H32
005761900	3.406	3.000	AN3H33
005790205	4.031	3.625	AN3H40
005828789	5.531	5.125	AN3H54

**Steel, Cadmium Plated, Drilled Head
125,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001822056	0.469	0.062	AN3H3A
001822057	0.531	0.125	AN3H4A
001822058	0.656	0.250	AN3H5A
001822059	0.781	0.375	AN3H6A
001822060	0.906	0.500	AN3H7A
001822061	1.031	0.625	AN3H10A
001822062	1.156	0.750	AN3H11A
001822063	1.281	0.875	AN3H12A
001822064	1.406	1.000	AN3H13A
001822005	1.531	1.125	AN3H14A
001822006	1.656	1.250	AN3H15A
001822007	1.781	1.375	AN3H16A
001822008	1.906	1.500	AN3H17A
001822009	2.031	1.625	AN3H20A
001822010	2.156	1.750	AN3H21A
001822011	2.281	1.875	AN3H22A
001822012	2.406	2.000	AN3H23A
001822013	2.531	2.125	AN3H25A
002825821	2.781	2.375	AN3H26A
002825843	2.906	2.500	AN3H27A
002825880	3.031	2.625	AN3H30A
002820904	3.156	2.750	AN3H31A
005500486	3.281	2.875	AN3H32A
005500703	3.531	3.125	AN3H34A
002852610	3.656	3.250	AN3H35A
006385777	3.781	3.375	AN3H36A
005598141	3.906	3.500	AN3H37A
005826678	4.031	3.625	AN3H40A
002825878	4.281	3.875	AN3H42A
006135504	4.406	4.000	AN3H43A
005598140	4.531	4.125	AN3H44A
011328493	4.906	4.500	AN3H47A
011530215	6.156	5.750	AN3H61A

**Corrosion-Resistant Steel, Passivated, Drilled Shank
125,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001457053	0.469	0.062	AN3C3
001457069	0.531	0.125	AN3C4
001457021	0.781	0.375	AN3C6
001457022	0.906	0.500	AN3C7
001457024	1.031	0.625	AN3C10
001443596	1.156	0.750	AN3C11
001457025	1.281	0.875	AN3C12
001443595	1.406	1.000	AN3C13
001457027	1.531	1.125	AN3C14
001457026	1.656	1.250	AN3C15
001512158	1.781	1.375	AN3C16
001821968	1.906	1.500	AN3C17
001822031	2.031	1.625	AN3C20
001822065	2.156	1.750	AN3C21
001822032	2.281	1.875	AN3C22
001822033	2.406	2.000	AN3C23
001822034	2.531	2.125	AN3C24
005793555	2.656	2.250	AN3C25
002759642	2.781	2.375	AN3C26
005159293	2.906	2.500	AN3C27

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
005793549	3.156	2.750	AN3C31
005793713	3.531	3.125	AN3C34
005793531	3.781	3.375	AN3C36
012067173	4.406	4.000	AN3C43
002089034	6.531	6.125	AN3C64

**Corrosion-Resistant Steel, Passivated, Undrilled
125,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001562336	0.469	0.062	AN3C3A
001509528	0.531	0.125	AN3C4A
001509527	0.656	0.250	AN3C5A
001562327	0.781	0.375	AN3C6A
001562328	0.906	0.500	AN3C7A
001562329	1.031	0.625	AN3C10A
001562330	1.156	0.750	AN3C11A
001562331	1.281	0.875	AN3C12A
001562332	1.406	1.000	AN3C13A
001562333	1.531	1.125	AN3C14A
001562334	1.656	1.250	AN3C15A
001562335	1.781	1.375	AN3C16A
001801929	1.906	1.500	AN3C17A
001801930	2.031	1.625	AN3C20A
001801931	2.156	1.750	AN3C21A
001801932	2.281	1.875	AN3C22A
001801933	2.406	2.000	AN3C23A
001801934	2.531	2.125	AN3C24A
002083632	2.656	2.250	AN3C25A
001744076	2.781	2.375	AN3C26A
002759641	2.906	2.500	AN3C27A
002083633	3.031	2.625	AN3C30A
006388237	3.156	2.750	AN3C31A
002071689	3.281	2.875	AN3C32A
005829723	3.406	3.000	AN3C33A
005157096	3.531	3.125	AN3C34A
006388194	3.656	3.250	AN3C35A
010209473	3.781	3.375	AN3C36A
005829724	3.906	3.500	AN3C37A
006378577	4.031	3.625	AN3C40A
005848759	4.156	3.750	AN3C41A
005829725	4.281	3.875	AN3C42A
002822657	4.906	4.500	AN3C47A
005829889	5.031	4.625	AN3C50A
005157097	5.406	5.000	AN3C53A
005157098	5.531	5.125	AN3C54A
005844975	6.781	6.375	AN3C66A
005844889	7.656	7.250	AN3C75A

**Corrosion-Resistant Steel, Passivated, Drilled Head and Shank
125,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
002824313	0.469	0.062	AN3CH3
001822040	0.531	0.125	AN3CH4
001822041	0.656	0.250	AN3CH5
001802731	0.781	0.375	AN3CH6
001802732	0.906	0.500	AN3CH7
001822042	1.031	0.625	AN3CH10
001822043	1.156	0.750	AN3CH11
001822044	1.281	0.875	AN3CH12
001822047	1.406	1.000	AN3CH13
001822048	1.531	1.125	AN3CH14
001821804	1.656	1.250	AN3CH15
001821811	2.531	2.125	AN3CH24
005845476	3.031	2.625	AN3CH30
005845626	3.906	3.500	AN3CH37
005828847	7.156	6.750	AN3CH71

**Corrosion-Resistant Steel, Passivated, Drilled Head
125,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001802769	0.469	0.062	AN3CH3A
001821853	0.531	0.125	AN3CH4A
001821854	0.656	0.250	AN3CH5A
001821855	0.781	0.375	AN3CH6A
001821856	0.906	0.500	AN3CH7A
001821857	1.031	0.625	AN3CH10A
001821858	1.156	0.750	AN3CH11A
001802770	1.281	0.875	AN3CH12A
001802771	1.406	1.000	AN3CH13A
001802772	1.531	1.125	AN3CH14A
001802773	1.656	1.250	AN3CH15A
001802774	1.781	1.375	AN3CH16A
001821946	2.031	1.625	AN3CH20A
001821947	2.281	1.875	AN3CH22A
005826828	2.781	2.375	AN3CH26A
005826829	2.906	2.500	AN3CH27A
005848760	3.531	3.125	AN3CH34A
005845479	3.781	3.375	AN3CH36A
005761960	3.906	3.500	AN3CH37A
005845480	4.031	3.625	AN3CH40A
005845592	4.656	4.250	AN3CH45A
002350603	6.031	5.625	AN3CH60A

**Aluminum Alloy, Anodized, Drilled Shank
62,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001511662	0.469	0.062	AN3DD3
001511661	0.531	0.125	AN3DD4
001511660	0.656	0.250	AN3DD5
001511659	0.781	0.375	AN3DD6
001511658	0.906	0.500	AN3DD7
001511656	1.156	0.750	AN3DD11
001511654	1.406	1.000	AN3DD13
001444017	1.531	1.125	AN3DD14
001511652	2.031	1.625	AN3DD20
001509854	2.156	1.750	AN3DD21
001509852	2.406	2.000	AN3DD23
001509851	2.531	2.125	AN3DD24
001511694	3.656	3.250	AN3DD35

**Aluminum Alloy, Anodized, Undrilled
62,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001457666	0.469	0.062	AN3DD3A
001457665	0.531	0.125	AN3DD4A
001457056	0.656	0.250	AN3DD5A
001457061	0.781	0.375	AN3DD6A
001457072	0.906	0.500	AN3DD7A
001457058	1.031	0.625	AN3DD12A
001512178	1.406	1.000	AN3DD13A
001512185	1.531	1.125	AN3DD14A
001512184	1.781	1.375	AN3DD16A
001512176	1.906	1.500	AN3DD17A
001512183	2.031	1.625	AN3DD20A
001512175	2.156	1.750	AN3DD21A
001512182	2.281	1.875	AN3DD22A
001512174	2.406	2.000	AN3DD23A
001512173	2.531	2.125	AN3DD24A
001512172	2.781	2.375	AN3DD26A
001512171	3.031	2.625	AN3DD30A
001512179	3.156	2.750	AN3DD31A
001457663	3.281	2.875	AN3DD32A
001457670	3.406	3.000	AN3DD33A
001512159	3.781	3.375	AN3DD36A
001457668	3.906	3.500	AN3DD37A
001277230	4.281	3.875	AN3DD42A
002825818	4.781	4.375	AN3DD46A
002822639	5.281	4.875	AN3DD52A
002759639	6.531	6.125	AN3DD64A

**Aluminum Alloy, Anodized, Drilled Head and Shank
62,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
002759637	0.531	0.125	AN3DDH4
002759696	0.781	0.375	AN3DDH6
005766845	1.281	0.875	AN3DDH12

**Aluminum Alloy, Anodized, Drilled Head
62,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
002066281	0.469	0.062	AN3DDH3A
002818936	0.531	0.125	AN3DDH4A
005598134	0.656	0.250	AN3DDH5A
006381476	1.156	0.750	AN3DDH11A
005516996	1.281	0.875	AN3DDH12A
005509134	1.406	1.000	AN3DDH13A
002268248	1.531	1.125	AN3DDH14A
005825754	1.656	1.250	AN3DDH15A
006378583	1.906	1.500	AN3DDH17A
005159295	3.281	2.875	AN3DDH32A

For additional assistance please contact: AVN Testing Office PVT
Workflow AVNTestingOfficePVTWorkflow@dla.mil

[<- Table of Contents](#)

Specification AN4

Hexagon Head

Head Width 0.478 Inch, Head Height 0.156 Inch

1/4-28 UNF-3A Threads

- [Steel, Cadmium Plated, Drilled Shank - 125,000 psi Tensile Strength](#)
 - [Steel, Cadmium Plated, Undrilled - 125,000 psi Tensile Strength](#)
 - [Steel, Cadmium Plated, Drilled Head and Shank - 125,000 psi Tensile Strength](#)
 - [Steel, Cadmium Plated, Drilled Head - 125,000 psi Tensile Strength](#)
 - [Corrosion-Resistant Steel, Passivated, Drilled Shank - 125,000 psi Tensile Strength](#)
 - [Corrosion-Resistant Steel, Passivated, Undrilled - 125,000 psi Tensile Strength](#)
 - [Corrosion-Resistant Steel, Passivated, Drilled Head and Shank - 125,000 psi Tensile Strength](#)
 - [Corrosion-Resistant Steel, Passivated, Drilled Head - 125,000 psi Tensile Strength](#)
 - [Aluminum Alloy, Anodized, Drilled Shank - 62,000 psi Tensile Strength](#)
 - [Aluminum Alloy, Anodized, Undrilled - 62,000 psi Tensile Strength](#)
 - [Aluminum Alloy, Anodized, Drilled Head and Shank - 62,000 psi Tensile Strength](#)
 - [Aluminum Alloy, Anodized, Drilled Head - 62,000 psi Tensile Strength](#)
-

Steel, Cadmium Plated, Drilled Shank

125,000 psi Tensile Strength

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001744111	0.469	0.062	AN4-3
001443703	0.531	0.062	AN4-4
001443704	0.656	0.188	AN4-5
001443705	0.781	0.312	AN4-6
001443706	0.906	0.438	AN4-7
001443707	1.031	0.562	AN4-10
001443708	1.156	0.688	AN4-11
001443709	1.281	0.812	AN4-12
001443710	1.406	0.938	AN4-13
001512666	1.656	1.188	AN4-15
001512665	1.781	1.312	AN4-16
001511006	1.906	1.438	AN4-17
001511004	2.156	1.688	AN4-21
001511003	2.281	1.812	AN4-22
001511002	2.406	1.938	AN4-23
001511144	2.656	2.188	AN4-25
001511143	2.781	2.312	AN4-26
001511142	2.906	2.438	AN4-27
006221823	3.156	2.688	AN4-31
001511138	3.406	2.938	AN4-33
001511137	3.531	3.062	AN4-34
001511135	3.781	3.312	AN4-36
001511134	3.906	3.438	AN4-37
001511132	4.156	3.688	AN4-41
001511131	4.281	3.812	AN4-42
001511130	4.406	3.938	AN4-43
001511129	4.531	4.062	AN4-44
001511128	4.656	4.188	AN4-45
001511127	4.781	4.312	AN4-46
001511126	4.906	4.438	AN4-47
001511125	5.031	4.562	AN4-50
001511124	5.156	4.688	AN4-51

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001511744	5.781	5.312	AN4-56
001511743	5.906	5.438	AN4-57
001511742	6.031	5.562	AN4-60
001511740	6.281	5.812	AN4-62
001511738	6.531	6.062	AN4-64
001511736	6.781	6.312	AN4-66
001511735	6.906	6.438	AN4-67
001511734	7.031	6.562	AN4-70
001511732	7.281	6.812	AN4-72
001511731	7.531	7.062	AN4-74
001511729	7.781	7.312	AN4-76
001511727	8.031	7.562	AN4-80

**Steel, Cadmium Plated, Undrilled
125,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001509105	0.531	0.062	AN4-4A
001511427	0.656	0.188	AN4-5A
001511426	0.781	0.312	AN4-6A
005158064	0.906	0.438	AN4-7A
001511424	1.031	0.562	AN4-10A
001511423	1.156	0.688	AN4-11A
001511422	1.281	0.812	AN4-12A
001511421	1.406	0.938	AN4-13A
001511420	1.531	1.062	AN4-14A
001511419	1.656	1.188	AN4-15A
001511418	1.781	1.312	AN4-16A
001511417	1.906	1.438	AN4-17A
001511416	2.031	1.562	AN4-20A
001511415	2.156	1.688	AN4-21A
001511414	2.281	1.812	AN4-22A
001511413	2.406	1.938	AN4-23A
001511412	2.531	2.062	AN4-24A
001511411	2.656	2.188	AN4-25A
001511410	2.781	2.312	AN4-26A
001511409	2.906	2.438	AN4-27A
001511408	3.031	2.562	AN4-30A
001511407	3.156	2.688	AN4-31A
001511406	3.281	2.812	AN4-32A
001511405	3.406	2.938	AN4-33A
001511404	3.531	3.062	AN4-34A
001511403	3.656	3.188	AN4-35A
001511402	3.781	3.312	AN4-36A
001511401	3.906	3.438	AN4-37A
001510450	4.031	3.562	AN4-40A
001510457	4.156	3.688	AN4-41A
001510456	4.281	3.812	AN4-42A
001510455	4.406	3.938	AN4-43A
001510452	4.781	4.312	AN4-46A
001510451	4.906	4.438	AN4-47A
001511100	5.031	4.562	AN4-50A
001511098	5.281	4.812	AN4-52A
001511097	5.406	4.938	AN4-53A
001511096	5.531	5.062	AN4-54A
001511095	5.656	5.188	AN4-55A
001511094	5.781	5.312	AN4-56A
001511294	6.031	5.562	AN4-60A
001511293	6.156	5.688	AN4-61A
001511292	6.281	5.812	AN4-62A
001511291	6.406	5.938	AN4-63A

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001511290	6.531	6.062	AN4-64A
001511289	6.656	6.188	AN4-65A
001511288	6.781	6.312	AN4-66A
001511287	6.906	6.438	AN4-67A
001511286	7.031	6.562	AN4-70A
001509110	7.531	7.062	AN4-74A
001509108	7.781	7.312	AN4-76A
001509107	7.906	7.438	AN4-77A
001509106	8.031	7.562	AN4-80A

Steel, Cadmium Plated, Drilled Head and Shank
125,000 psi Tensile Strength

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001821924	0.469	0.062	AN4H3
001821925	0.531	0.062	AN4H4
001821926	0.656	0.188	AN4H5
001821526	0.781	0.312	AN4H6
001821527	0.906	0.438	AN4H7
001821528	1.031	0.562	AN4H10
001821529	1.156	0.688	AN4H11
001821530	1.281	0.812	AN4H12
001821531	1.406	0.938	AN4H13
001803349	1.531	1.062	AN4H14
001803350	1.656	1.188	AN4H15
006388223	1.781	1.312	AN4H16
001821912	1.906	1.438	AN4H17
001821913	2.031	1.562	AN4H20
006388206	2.156	1.688	AN4H21
001802705	2.281	1.812	AN4H22
001802706	2.406	1.938	AN4H23
001802707	2.531	2.062	AN4H24
001802708	2.656	2.188	AN4H25
001802709	2.781	2.312	AN4H26
006388178	2.906	2.438	AN4H27
001802711	3.031	2.562	AN4H30
005589453	3.156	2.688	AN4H31
005589452	3.281	2.812	AN4H32
006395993	3.406	2.938	AN4H33
006385784	3.656	3.188	AN4H35
005826635	3.906	3.438	AN4H37
005589458	4.031	3.562	AN4H40
005589457	4.156	3.688	AN4H41
005826916	4.281	3.812	AN4H42
005589456	4.406	3.938	AN4H43
012822352	4.531	4.062	AN4H44
005826914	4.656	4.188	AN4H45
005826913	4.781	4.312	AN4H46
005589454	5.031	4.562	AN4H50
012060087	5.156	4.688	AN4H51
008198898	5.281	4.812	AN4H52
006385829	5.531	5.062	AN4H54
012822334	6.531	6.062	AN4H64
012822351	7.031	6.562	AN4H70
012822360	8.031	7.562	AN4H80

**Steel, Cadmium Plated, Drilled Head
125,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001822014	0.469	0.062	AN4H3A
001822016	0.656	0.188	AN4H5A
001822017	0.781	0.312	AN4H6A
002928252	0.906	0.438	AN4H7A
001821958	1.031	0.562	AN4H10A
001821959	1.156	0.688	AN4H11A
001821960	1.281	0.812	AN4H12A
001821961	1.406	0.938	AN4H13A
001821962	1.531	1.062	AN4H14A
001821963	1.656	1.188	AN4H15A
001821964	1.781	1.312	AN4H16A
001821965	1.906	1.438	AN4H17A
001821966	2.031	1.562	AN4H20A
001803360	2.156	1.688	AN4H21A
001822038	2.281	1.812	AN4H22A
001822039	2.406	1.938	AN4H23A
001822018	2.531	2.062	AN4H24A
001822019	2.656	2.188	AN4H25A
001822020	2.781	2.312	AN4H26A
001822021	2.906	2.438	AN4H27A
001822022	3.031	2.562	AN4H30A
006385809	3.156	2.688	AN4H31A
005589467	3.281	2.812	AN4H32A
002079791	3.406	2.938	AN4H33A
006385766	3.531	3.062	AN4H34A
002818945	3.656	3.188	AN4H35A
005767739	3.781	3.312	AN4H36A
005761907	3.906	3.438	AN4H37A
006385753	4.031	3.562	AN4H40A
005311534	4.156	3.688	AN4H41A
002822675	4.281	3.812	AN4H42A
002822678	4.406	3.938	AN4H43A
002822677	4.531	4.062	AN4H44A
001414714	4.656	4.188	AN4H45A
002822663	4.781	4.312	AN4H46A
005589455	4.906	4.438	AN4H47A
002822680	5.031	4.562	AN4H50A
006395994	5.156	4.688	AN4H51A
005589459	5.281	4.812	AN4H52A
008404320	5.781	5.312	AN4H56A
005846747	5.906	5.438	AN4H57A
005761941	6.031	5.562	AN4H60A
005761943	6.281	5.812	AN4H62A
002822679	6.531	6.062	AN4H64A
006163792	6.906	6.438	AN4H67A
008354442	7.906	7.438	AN4H77A

**Corrosion-Resistant Steel, Passivated, Drilled Shank
125,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
006166600	0.469	0.062	AN4C3
001512550	0.531	0.062	AN4C4
001512541	0.656	0.188	AN4C5
001512540	0.781	0.312	AN4C6
001512539	0.906	0.438	AN4C7
001512538	1.031	0.562	AN4C10
001512537	1.156	0.688	AN4C11
001512800	1.281	0.812	AN4C12
001512798	1.531	1.062	AN4C14
001512797	1.656	1.188	AN4C15
001512796	1.781	1.312	AN4C16
001512795	1.906	1.438	AN4C17
001562277	2.031	1.562	AN4C20
001562278	2.156	1.688	AN4C21
001562279	2.281	1.812	AN4C22
001512447	2.406	1.938	AN4C23
001512446	2.531	2.062	AN4C24
001512445	2.656	2.188	AN4C25
001512444	2.781	2.312	AN4C26
001512443	2.906	2.438	AN4C27
001512442	3.031	2.562	AN4C30
001800060	4.031	3.562	AN4C40
005159294	4.281	3.812	AN4C42
002759649	4.531	4.062	AN4C44
012849664	4.656	4.188	AN4C45
004492926	5.406	4.938	AN4C53
002759648	5.531	5.062	AN4C54
009223422	5.656	5.188	AN4C55
010170663	5.781	5.312	AN4C56
009495483	6.031	5.562	AN4C60
000389070	6.281	5.812	AN4C62
001512140	6.406	5.938	AN4C63
000409505	6.781	6.312	AN4C66
009907835	7.781	7.312	AN4C76

**Corrosion-Resistant Steel, Passivated, Undrilled
125,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
002065745	0.469	0.062	AN4C3A
001509873	0.531	0.062	AN4C4A
001562337	0.656	0.188	AN4C5A
001562338	0.781	0.312	AN4C6A
001562339	0.906	0.438	AN4C7A
001562340	1.031	0.562	AN4C10A
001562341	1.156	0.688	AN4C11A
001562342	1.281	0.812	AN4C12A
001562343	1.406	0.938	AN4C13A
001562344	1.531	1.062	AN4C14A
001562345	1.656	1.188	AN4C15A
001562346	1.781	1.312	AN4C16A
001562347	1.906	1.438	AN4C17A
001562348	2.031	1.562	AN4C20A
001562349	2.156	1.688	AN4C21A
001509866	2.281	1.812	AN4C22A
001509867	2.406	1.938	AN4C23A
001509868	2.531	2.062	AN4C24A
001509869	2.656	2.188	AN4C25A
001509871	2.906	2.438	AN4C27A
001509872	3.031	2.562	AN4C30A
005844888	3.156	2.688	AN4C31A
006392460	3.281	2.812	AN4C32A
005844887	3.406	2.938	AN4C33A
002824111	3.531	3.062	AN4C34A
002825833	3.656	3.188	AN4C35A
002822212	3.781	3.312	AN4C36A
001744094	3.906	3.438	AN4C37A
006395992	4.031	3.562	AN4C40A
005844886	4.156	3.688	AN4C41A
005848425	4.406	3.938	AN4C43A
005435079	4.906	4.438	AN4C47A
010211848	5.031	4.562	AN4C50A
013195179	5.531	5.062	AN4C54A
008249256	5.656	5.188	AN4C55A
000389067	6.031	5.562	AN4C60A
001414712	7.156	6.688	AN4C71A
001744087	7.406	6.938	AN4C73A

**Corrosion-Resistant Steel, Passivated, Drilled Head and Shank
125,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
005503744	0.531	0.062	AN4CH4
001821812	0.469	0.062	AN4CH3
001803346	0.656	0.188	AN4CH5
001821524	0.781	0.312	AN4CH6
001821525	0.906	0.438	AN4CH7
001803347	1.031	0.562	AN4CH10
001803348	1.156	0.688	AN4CH11
001803353	1.281	0.812	AN4CH12
001803354	1.406	0.938	AN4CH13
001821776	1.531	1.062	AN4CH14
001821777	1.656	1.188	AN4CH15
001821778	1.781	1.312	AN4CH16
001821779	1.906	1.438	AN4CH17
001821781	2.156	1.688	AN4CH21
001821785	2.656	2.188	AN4CH25

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001821788	3.031	2.562	AN4CH30
002822666	3.281	2.812	AN4CH32
002825835	3.406	2.938	AN4CH33
005826626	3.531	3.062	AN4CH34
005826625	3.656	3.188	AN4CH35
002928749	4.031	3.562	AN4CH40
012822346	6.031	5.562	AN4CH60

**Corrosion-Resistant Steel, Passivated, Drilled Head
125,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001802777	0.469	0.062	AN4CH3A
001802778	0.531	0.062	AN4CH4A
001802779	0.656	0.188	AN4CH5A
001821859	0.781	0.312	AN4CH6A
001821860	0.906	0.438	AN4CH7A
001801778	1.031	0.562	AN4CH10A
001803359	1.156	0.688	AN4CH11A
001802729	1.531	1.062	AN4CH14A
001802730	1.656	1.188	AN4CH15A
001821863	1.781	1.312	AN4CH16A
001821864	1.906	1.438	AN4CH17A
001821865	2.031	1.562	AN4CH20A
001821866	2.156	1.688	AN4CH21A
001821867	2.281	1.812	AN4CH22A
001821868	2.406	1.938	AN4CH23A
001821869	2.531	2.062	AN4CH24A
001821897	2.781	2.312	AN4CH26A
001802780	2.906	2.438	AN4CH27A
002825832	3.906	3.438	AN4CH37A
005826847	4.656	4.188	AN4CH45A

**Aluminum Alloy, Anodized, Drilled Shank
62,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001511642	0.531	0.062	AN4DD4
001511641	0.656	0.188	AN4DD5
001511640	0.781	0.312	AN4DD6
001511639	0.906	0.438	AN4DD7
001511638	1.031	0.562	AN4DD10
001511637	1.156	0.688	AN4DD11
001511636	1.281	0.812	AN4DD12
001511633	1.656	1.188	AN4DD15
001511632	1.781	1.312	AN4DD16
001511630	2.031	1.562	AN4DD20
001511628	2.281	1.812	AN4DD22
001511627	2.406	1.938	AN4DD23
001511626	2.531	2.062	AN4DD24
001511624	2.781	2.312	AN4DD26
001511623	2.906	2.438	AN4DD27
005501168	4.656	4.188	AN4DD45
001512118	5.031	4.562	AN4DD50
004994874	5.156	4.688	AN4DD51
004953234	6.031	5.562	AN4DD60
001373057	6.531	6.062	AN4DD64

**Aluminum Alloy, Anodized, Undrilled
62,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
002069578	0.469	0.062	AN4DD3A
001511076	0.531	0.062	AN4DD4A
001511057	0.656	0.188	AN4DD5A
001511056	0.781	0.312	AN4DD6A
001511055	0.906	0.438	AN4DD7A
001511054	1.031	0.562	AN4DD10A
001511053	1.156	0.688	AN4DD11A
001511448	1.656	1.188	AN4DD15A
001511446	1.906	1.438	AN4DD17A
001511445	2.031	1.562	AN4DD20A
001511444	2.156	1.688	AN4DD21A
001511443	2.281	1.812	AN4DD22A
001511442	2.406	1.938	AN4DD23A
001511441	2.531	2.062	AN4DD24A
001511440	2.656	2.188	AN4DD25A
001511439	2.781	2.312	AN4DD26A
001511438	2.906	2.438	AN4DD27A
001511437	3.031	2.562	AN4DD30A
001511436	3.281	2.812	AN4DD32A
001511434	3.531	3.062	AN4DD34A
001511433	3.656	3.188	AN4DD35A
001511432	3.781	3.312	AN4DD36A
006392404	4.156	3.688	AN4DD41A
001511075	4.281	3.812	AN4DD42A
001503227	4.406	3.938	AN4DD43A
004874896	4.906	4.438	AN4DD47A

**Aluminum Alloy, Anodized, Drilled Head and Shank
62,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
008117716	1.531	1.062	AN4DDH14

**Aluminum Alloy, Anodized, Drilled Head
62,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001744091	0.469	0.062	AN4DDH3A
002759643	0.531	0.062	AN4DDH4A
002089029	0.656	0.188	AN4DDH5A
002759644	0.781	0.312	AN4DDH6A
002925204	0.906	0.438	AN4DDH7A
005589447	1.031	0.562	AN4DDH10A
006385757	1.156	0.688	AN4DDH11A
005157527	1.281	0.812	AN4DDH12A
006559943	1.406	0.938	AN4DDH13A
008370490	1.656	1.188	AN4DDH15A
008171188	1.781	1.312	AN4DDH16A
008354471	2.031	1.562	AN4DDH20A
008103765	2.156	1.688	AN4DDH21A
005589446	2.781	2.312	AN4DDH26A
006559959	2.906	2.438	AN4DDH27A
008354437	3.531	3.062	AN4DDH34A
002822211	4.531	4.062	AN4DDH44A
008252209	4.906	4.438	AN4DDH47A
009484188	5.156	4.688	AN4DDH51A

Specification AN5

Hexagon Head

Head Width 0.500 Inch, Head Height 0.188 Inch

5/16-24 UNF-3A Threads

- [Steel, Cadmium Plated, Drilled Shank - 125,000 psi Tensile Strength](#)
 - [Steel, Cadmium Plated, Undrilled - 125,000 psi Tensile Strength](#)
 - [Steel, Cadmium Plated, Drilled Head and Shank - 125,000 psi Tensile Strength](#)
 - [Steel, Cadmium Plated, Drilled Head - 125,000 psi Tensile Strength](#)
 - [Corrosion-Resistant Steel, Passivated, Drilled Shank - 125,000 psi Tensile Strength](#)
 - [Corrosion-Resistant Steel, Passivated, Undrilled - 125,000 psi Tensile Strength](#)
 - [Corrosion-Resistant Steel, Passivated, Drilled Head and Shank - 125,000 psi Tensile Strength](#)
 - [Corrosion-Resistant Steel, Passivated, Drilled Head - 125,000 psi Tensile Strength](#)
 - [Aluminum Alloy, Anodized, Drilled Shank - 62,000 psi Tensile Strength](#)
 - [Aluminum Alloy, Anodized, Undrilled - 62,000 psi Tensile Strength](#)
 - [Aluminum Alloy, Anodized, Drilled Head and Shank - 62,000 psi Tensile Strength](#)
 - [Aluminum Alloy, Anodized, Drilled Head - 62,000 psi Tensile Strength](#)
-

Steel, Cadmium Plated, Drilled Shank

125,000 psi Tensile Strength

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001511726	0.594	0.062	AN5-4
001511725	0.719	0.188	AN5-5
008399642	0.844	0.312	AN5-6
001511723	0.969	0.438	AN5-7
001511722	1.094	0.562	AN5-10
001511720	1.344	0.812	AN5-12
001511719	1.469	0.938	AN5-13
001511718	1.594	1.062	AN5-14
001511716	1.844	1.312	AN5-16
001511715	1.969	1.438	AN5-17
001510919	2.344	1.812	AN5-22
001510918	2.469	1.938	AN5-23
001510916	2.719	2.188	AN5-25
001510915	2.844	2.312	AN5-26
001510914	2.969	2.438	AN5-27
001510912	3.219	2.688	AN5-31
001510910	3.469	2.938	AN5-33
001510909	3.594	3.062	AN5-34
001510908	3.719	3.188	AN5-35
001510907	3.844	3.312	AN5-36
001511324	4.219	3.688	AN5-41
001511306	4.344	3.812	AN5-42
001509393	4.719	4.188	AN5-45
001509392	4.844	4.312	AN5-46
001509391	4.969	4.438	AN5-47
001509390	5.094	4.562	AN5-50
001511610	5.469	4.938	AN5-53
001509387	5.594	5.062	AN5-54
001509384	5.969	5.438	AN5-57
001509383	6.094	5.562	AN5-60
001512548	6.344	5.812	AN5-62
001512547	6.469	5.938	AN5-63

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001511309	6.594	6.062	AN5-64
001511308	6.719	6.188	AN5-65
001511307	6.844	6.312	AN5-66
001511606	7.219	6.688	AN5-71
001511350	7.469	6.938	AN5-73
001511349	7.594	7.062	AN5-74
001511348	7.719	7.188	AN5-75
001511347	7.844	7.312	AN5-76
001511346	7.969	7.438	AN5-77
001511345	8.094	7.562	AN5-80

**Steel, Cadmium Plated, Undrilled
125,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
006161248	0.594	0.062	AN5-4A
001509104	0.719	0.188	AN5-5A
001509101	0.844	0.312	AN5-6A
001509102	0.969	0.438	AN5-7A
001457036	1.094	0.562	AN5-10A
001509103	1.219	0.688	AN5-11A
006162618	1.344	0.812	AN5-12A
001512626	1.469	0.938	AN5-13A
005274128	1.594	1.062	AN5-14A
001511284	1.594	1.062	AN5-14A
001511283	1.719	1.188	AN5-15A
001512625	1.844	1.312	AN5-16A
001512624	1.969	1.438	AN5-17A
001512623	2.094	1.562	AN5-20A
001512622	2.219	1.688	AN5-21A
001512621	2.344	1.812	AN5-22A
001512620	2.469	1.938	AN5-23A
001512619	2.594	2.062	AN5-24A
006165984	2.719	2.188	AN5-25A
001512617	2.844	2.312	AN5-26A
001512616	2.969	2.438	AN5-27A
001512615	3.094	2.562	AN5-30A
001512614	3.219	2.688	AN5-31A
001512613	3.344	2.812	AN5-32A
001512612	3.469	2.938	AN5-33A
001509236	3.594	3.062	AN5-34A
001509237	3.719	3.188	AN5-35A
001509235	3.844	3.312	AN5-36A
001509234	3.969	3.438	AN5-37A
001509233	4.094	3.562	AN5-40A
001509232	4.219	3.688	AN5-41A
001509231	4.344	3.812	AN5-42A
001511158	4.469	3.938	AN5-43A
001511157	4.594	4.062	AN5-44A
001511156	4.719	4.188	AN5-45A
001511155	4.844	4.312	AN5-46A
001511154	4.969	4.438	AN5-47A
001511153	5.094	4.562	AN5-50A
001511152	5.219	4.688	AN5-51A
001511151	5.344	4.812	AN5-52A
001511450	5.469	4.938	AN5-53A
001511000	5.594	5.062	AN5-54A
001510999	5.719	5.188	AN5-55A
001510998	5.844	5.312	AN5-56A
001510997	5.969	5.438	AN5-57A

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
008521819	6.094	5.562	AN5-60A
001509543	6.594	6.062	AN5-64A
001509542	6.719	6.188	AN5-65A
001509540	6.969	6.438	AN5-67A
002818478	7.844	7.312	AN5-76A
010795130	7.969	7.438	AN5-77A

Steel, Cadmium Plated, Drilled Head and Shank
125,000 psi Tensile Strength

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001802712	0.594	0.062	AN5H4
001821851	0.719	0.188	AN5H5
001821852	0.844	0.312	AN5H6
001802748	0.969	0.438	AN5H7
001802749	1.094	0.562	AN5H10
001802750	1.219	0.688	AN5H11
001802751	1.344	0.812	AN5H12
001802752	1.469	0.938	AN5H13
001802753	1.594	1.062	AN5H14
001802755	1.844	1.312	AN5H16
001802756	1.969	1.438	AN5H17
001802757	2.094	1.562	AN5H20
001802716	2.219	1.688	AN5H21
001802717	2.344	1.812	AN5H22
001802718	2.469	1.938	AN5H23
001802719	2.594	2.062	AN5H24
006391845	2.719	2.188	AN5H25
001802721	2.844	2.312	AN5H26
001802722	2.969	2.438	AN5H27
001802723	3.094	2.562	AN5H30
001802724	3.219	2.688	AN5H31
001802725	3.344	2.812	AN5H32
001802726	3.469	2.938	AN5H33
001802727	3.594	3.062	AN5H34
001802728	3.719	3.188	AN5H35
006377591	3.844	3.312	AN5H36
006392354	3.969	3.438	AN5H37
005589466	4.094	3.562	AN5H40
002928253	4.219	3.688	AN5H41
006384793	4.344	3.812	AN5H42
005589465	4.469	3.938	AN5H43
006385810	4.594	4.062	AN5H44
005589463	4.844	4.312	AN5H46
005589462	5.094	4.562	AN5H50
008154770	5.219	4.688	AN5H51
008348021	5.344	4.812	AN5H52
005589460	5.469	4.938	AN5H53
008103762	5.719	5.188	AN5H55
008154762	6.219	5.688	AN5H61

**Steel, Cadmium Plated, Drilled Head
125,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001822023	0.594	0.062	AN5H4A
001822024	0.719	0.188	AN5H5A
001822025	0.844	0.312	AN5H6A
001822026	0.969	0.438	AN5H7A
001822027	1.094	0.562	AN5H10A
001822028	1.219	0.688	AN5H11A
001822029	1.344	0.812	AN5H12A
001822030	1.469	0.938	AN5H13A
001822045	1.594	1.062	AN5H14A
001822046	1.719	1.188	AN5H15A
001802668	1.844	1.312	AN5H16A
001802669	1.969	1.438	AN5H17A
001802670	2.094	1.562	AN5H20A
001802671	2.219	1.688	AN5H21A
001802672	2.344	1.812	AN5H22A
001802673	2.469	1.938	AN5H23A
001802674	2.594	2.062	AN5H24A
001802675	2.719	2.188	AN5H25A
001802676	2.844	2.312	AN5H26A
001802677	2.969	2.438	AN5H27A
001802678	3.094	2.562	AN5H30A
001802679	3.219	2.688	AN5H31A
001802680	3.344	2.812	AN5H32A
001802683	3.719	3.188	AN5H35A
002822634	3.844	3.312	AN5H36A
002065741	3.969	3.438	AN5H37A
002822664	4.969	4.438	AN5H47A
010795128	5.469	4.938	AN5H53A
009435370	5.719	5.188	AN5H55A
002089059	5.844	5.312	AN5H56A

**Corrosion-Resistant Steel, Passivated, Drilled Shank
125,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001512459	0.594	0.062	AN5C4
001512441	0.719	0.188	AN5C5
001512440	0.844	0.312	AN5C6
001512439	0.969	0.438	AN5C7
001512438	1.094	0.562	AN5C10
001490956	1.344	0.812	AN5C12
001512436	1.469	0.938	AN5C13
001512433	1.844	1.312	AN5C16
001512432	1.969	1.438	AN5C17
001512431	2.094	1.562	AN5C20
001512468	2.219	1.688	AN5C21
001512467	2.344	1.812	AN5C22
001512466	2.469	1.938	AN5C23
001512464	2.719	2.188	AN5C25
001512463	2.844	2.312	AN5C26
001512462	2.969	2.438	AN5C27
001822035	3.344	2.812	AN5C32
001822036	3.594	3.062	AN5C34
001822037	3.719	3.188	AN5C35
006384886	4.094	3.562	AN5C40
001512460	4.219	3.688	AN5C41
002759665	5.594	5.062	AN5C54
013064177	6.594	6.062	AN5C64
012983119	6.719	6.188	AN5C65

**Corrosion-Resistant Steel, Passivated, Undrilled
125,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001801935	0.594	0.062	AN5C4A
001801936	0.719	0.188	AN5C5A
001801937	0.844	0.312	AN5C6A
001673685	0.969	0.438	AN5C7A
001801919	1.094	0.562	AN5C10A
001801920	1.219	0.688	AN5C11A
001801921	1.344	0.812	AN5C12A
001801922	1.469	0.938	AN5C13A
001801923	1.594	1.062	AN5C14A
001801924	1.719	1.188	AN5C15A
001801925	1.844	1.312	AN5C16A
001801926	1.969	1.438	AN5C17A
001801927	2.094	1.562	AN5C20A
001801928	2.219	1.688	AN5C21A
001801938	2.344	1.812	AN5C22A
001801949	2.469	1.938	AN5C23A
001821512	2.594	2.062	AN5C24A
001821514	2.844	2.312	AN5C26A
001801939	2.969	2.438	AN5C27A
001775674	3.219	2.688	AN5C31A
001801943	3.469	2.938	AN5C33A
005829455	3.844	3.312	AN5C36A
005828551	3.969	3.438	AN5C37A
010591900	4.219	3.688	AN5C41A
011881634	4.844	4.312	AN5C46A
005828850	4.969	4.438	AN5C47A
008350808	5.094	4.562	AN5C50A
011121550	5.844	5.312	AN5C56A
012983118	6.219	5.688	AN5C61A
008352085	6.844	6.312	AN5C66A
008353080	7.344	6.812	AN5C72A

**Corrosion-Resistant Steel, Passivated, Drilled Head and Shank
125,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001821814	0.719	0.188	AN5CH5
001821815	0.844	0.312	AN5CH6
001821816	0.969	0.438	AN5CH7
001821817	1.094	0.562	AN5CH10
001803357	1.219	0.688	AN5CH11
001803358	1.344	0.812	AN5CH12
001821849	1.469	0.938	AN5CH13
001821850	1.594	1.062	AN5CH14
001821931	1.719	1.188	AN5CH15
001821932	1.844	1.312	AN5CH16
002823925	1.969	1.438	AN5CH17
001821938	2.594	2.062	AN5CH24
001821942	3.094	2.562	AN5CH30
001821943	3.219	2.688	AN5CH31
006807410	5.219	4.688	AN5CH51

**Corrosion-Resistant Steel, Passivated, Drilled Head
125,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001802782	0.594	0.062	AN5CH4A
001802783	0.719	0.188	AN5CH5A
001821949	0.844	0.312	AN5CH6A
001821950	0.969	0.438	AN5CH7A
001821951	1.094	0.562	AN5CH10A
001821952	1.219	0.688	AN5CH11A
001822051	1.469	0.938	AN5CH13A
001822052	1.594	1.062	AN5CH14A
001802733	1.969	1.438	AN5CH17A
001802734	2.094	1.562	AN5CH20A
011601944	2.469	1.938	AN5CH23A
013553662	2.719	2.188	AN5CH25A
001822055	3.719	3.188	AN5CH35A
008500762	6.094	5.562	AN5CH60A

**Aluminum Alloy, Anodized, Drilled Shank
62,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001512123	0.844	0.312	AN5DD6
001512125	1.094	0.562	AN5DD10
001512126	1.219	0.688	AN5DD11
001512127	1.344	0.812	AN5DD12
001512128	1.469	0.938	AN5DD13
001512133	2.094	1.562	AN5DD20
011639277	5.469	4.938	AN5DD53

**Aluminum Alloy, Anodized, Undrilled
62,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
002823354	0.594	0.062	AN5DD4A
001510708	0.719	0.188	AN5DD5A
001511070	0.844	0.312	AN5DD6A
001511069	0.969	0.438	AN5DD7A
001511068	1.094	0.562	AN5DD10A
002820937	1.219	0.688	AN5DD11A
002759629	1.469	0.938	AN5DD13A
001510707	2.094	1.562	AN5DD20A
001510705	2.344	1.812	AN5DD22A
007215983	2.469	1.938	AN5DD23A
012941712	3.344	2.812	AN5DD32A
001510989	3.844	3.312	AN5DD36A
012895851	3.969	3.438	AN5DD37A

**Aluminum Alloy, Anodized, Drilled Head and Shank
62,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
006392347	0.844	0.312	AN5DDH6

**Aluminum Alloy, Anodized, Drilled Head
62,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001136240	0.594	0.062	AN5DDH4A
001312645	0.969	0.438	AN5DDH7A
005848285	1.344	0.812	AN5DDH12A

**For additional assistance please contact: AVN Testing Office PVT
Workflow AVNTestingOfficePVTWorkflow@dla.mil**

[<- Table of Contents](#)

Specification AN6
Hexagon Head
Head Width 0.562 Inch,
Head Height 0.218 Inch
3/8-24 UNF-3A Threads

- [Steel, Cadmium Plated, Drilled Shank - 125,000 psi Tensile Strength](#)
 - [Steel, Cadmium Plated, Undrilled - 125,000 psi Tensile Strength](#)
 - [Steel, Cadmium Plated, Drilled Head and Shank - 125,000 psi Tensile Strength](#)
 - [Steel, Cadmium Plated, Drilled Head - 125,000 psi Tensile Strength](#)
 - [Corrosion-Resistant Steel, Passivated, Drilled Shank - 125,000 psi Tensile Strength](#)
 - [Corrosion-Resistant Steel, Passivated, Undrilled - 125,000 psi Tensile Strength](#)
 - [Corrosion-Resistant Steel, Passivated, Drilled Head and Shank - 125,000 psi Tensile Strength](#)
 - [Corrosion-Resistant Steel, Passivated, Drilled Head - 125,000 psi Tensile Strength](#)
 - [Aluminum Alloy, Anodized, Drilled Shank - 62,000 psi Tensile Strength](#)
 - [Aluminum Alloy, Anodized, Undrilled 62,000 psi Tensile Strength](#)
 - [Aluminum Alloy, Anodized, Drilled Head and Shank - 62,000 psi Tensile Strength](#)
 - [Aluminum Alloy, Anodized, Drilled Head - 62,000 psi Tensile Strength](#)
-

Steel, Cadmium Plated, Drilled Shank
125,000 psi Tensile Strength

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001511344	0.703	0.062	AN6-5
001511343	0.828	0.188	AN6-6
001511341	1.078	0.438	AN6-10
001511340	1.203	0.562	AN6-11
001511339	1.328	0.688	AN6-12
001511338	1.453	0.812	AN6-13
001511337	1.578	0.938	AN6-14
001511336	1.703	1.062	AN6-15
001511335	1.828	1.188	AN6-16
006849781	1.953	1.312	AN6-17
001673686	2.078	1.438	AN6-20
001673687	2.203	1.562	AN6-21
001673688	2.328	1.688	AN6-22
001673689	2.453	1.812	AN6-23
001673690	2.578	1.938	AN6-24
001673691	2.703	2.062	AN6-25
001673692	2.828	2.188	AN6-26
001673693	2.953	2.312	AN6-27
001673694	3.078	2.438	AN6-30
001673695	3.203	2.562	AN6-31
001673696	3.328	2.688	AN6-32
001673697	3.453	2.812	AN6-33
001673699	3.703	3.062	AN6-35
001673700	3.828	3.188	AN6-36
001673701	3.953	3.312	AN6-37
001673702	4.078	3.438	AN6-40
001673703	4.203	3.562	AN6-41
001673705	4.453	3.812	AN6-43
001673706	4.578	3.938	AN6-44
001673707	4.703	4.062	AN6-45
001673708	4.828	4.188	AN6-46
001673709	4.953	4.312	AN6-47

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001673710	5.078	4.438	AN6-50
001673711	5.203	4.562	AN6-51
001673712	5.328	4.688	AN6-52
001673713	5.453	4.812	AN6-53
001673714	5.578	4.938	AN6-54
001673715	5.703	5.062	AN6-55
001673716	5.828	5.188	AN6-56
001673717	5.953	5.312	AN6-57
001673718	6.078	5.438	AN6-60
001673719	6.203	5.562	AN6-61
001673859	6.453	5.812	AN6-63
001673860	6.578	5.938	AN6-64
001673861	6.703	6.062	AN6-65
001673862	6.828	6.188	AN6-66
001673863	6.953	6.312	AN6-67
001673864	7.078	6.438	AN6-70
001673865	7.203	6.562	AN6-71
001673867	7.453	6.812	AN6-73
001673868	7.578	6.938	AN6-74
001512092	7.828	7.188	AN6-76
001512069	8.078	7.438	AN6-80

Steel, Cadmium Plated, Undrilled
125,000 psi Tensile Strength

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001800238	0.703	0.062	AN6-5A
006161224	0.828	0.188	AN6-6A
005318979	0.953	0.312	AN6-7A
002083636	1.078	0.438	AN6-10A
001801483	1.203	0.562	AN6-11A
001444004	1.328	0.688	AN6-12A
001801485	1.453	0.812	AN6-13A
002062865	1.578	0.938	AN6-14A
001801487	1.703	1.062	AN6-15A
002083639	1.828	1.188	AN6-16A
001801489	1.953	1.312	AN6-17A
002818477	2.078	1.438	AN6-20A
002083654	2.203	1.562	AN6-21A
002089806	2.328	1.688	AN6-22A
002083666	2.453	1.812	AN6-23A
001800304	2.578	1.938	AN6-24A
002078362	2.703	2.062	AN6-25A
001800306	2.953	2.312	AN6-27A
005826411	3.078	2.438	AN6-30A
001800309	3.203	2.562	AN6-31A
001800310	3.328	2.688	AN6-32A
002086090	3.453	2.812	AN6-33A
001800312	3.578	2.938	AN6-34A
001800313	3.703	3.062	AN6-35A
005826692	3.828	3.188	AN6-36A
002759560	3.953	3.312	AN6-37A
002759561	4.078	3.438	AN6-40A
008394832	4.203	3.562	AN6-41A
001803323	4.328	3.688	AN6-42A
001801452	4.453	3.812	AN6-43A
002759544	4.578	3.938	AN6-44A
001450934	4.703	4.062	AN6-45A
002759547	4.828	4.188	AN6-46A

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
003288906	4.953	4.312	AN6-47A
007207666	5.078	4.438	AN6-50A
007214426	5.203	4.562	AN6-51A
002759554	5.328	4.688	AN6-52A
007029634	5.578	4.938	AN6-54A
007226126	5.703	5.062	AN6-55A
008443115	5.828	5.188	AN6-56A
008223184	5.953	5.312	AN6-57A
004380648	6.078	5.438	AN6-60A
009907836	6.203	5.562	AN6-61A
010260733	6.453	5.812	AN6-63A
006208291	6.578	5.938	AN6-64A
007276770	6.828	6.188	AN6-66A
008361181	7.078	6.438	AN6-70A
011992271	7.203	6.562	AN6-71A
009717708	7.328	6.688	AN6-72A
001503516	7.578	6.938	AN6-74A
010894305	7.953	7.312	AN6-77A

**Steel, Cadmium Plated, Drilled Head and Shank
125,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
006387511	0.703	0.062	AN6H5
002820895	0.828	0.188	AN6H6
006378591	0.953	0.312	AN6H7
006385775	1.078	0.438	AN6H10
006384834	1.203	0.562	AN6H11
002819995	1.328	0.688	AN6H12
006385760	1.453	0.812	AN6H13
002089036	1.578	0.938	AN6H14
002819996	1.953	1.312	AN6H17
002825822	2.203	1.562	AN6H21
002825823	2.328	1.688	AN6H22
002069577	2.703	2.062	AN6H25
006385307	2.953	2.312	AN6H27
002819999	3.078	2.438	AN6H30
002820000	3.203	2.562	AN6H31
006398438	3.453	2.812	AN6H33
006383411	3.578	2.938	AN6H34
006389033	3.953	3.312	AN6H37
006385759	4.078	3.438	AN6H40
002861522	4.453	3.812	AN6H43
008210891	4.578	3.938	AN6H44
006161569	5.078	4.438	AN6H50
012759924	5.203	4.562	AN6H51
008577036	5.453	4.812	AN6H53
010144222	5.703	5.062	AN6H55
012759914	6.453	5.812	AN6H63
005767738	6.578	5.938	AN6H64

**Steel, Cadmium Plated, Drilled Head
125,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
002852586	0.703	0.062	AN6H5A
006385828	0.828	0.188	AN6H6A
002066266	0.953	0.312	AN6H7A
007214984	1.203	0.562	AN6H11A
002066270	1.328	0.688	AN6H12A
002064185	1.453	0.812	AN6H13A
006385832	1.578	0.938	AN6H14A
005828919	1.703	1.062	AN6H15A
005828918	1.828	1.188	AN6H16A
007376759	1.953	1.312	AN6H17A
005828917	2.078	1.438	AN6H20A
005828916	2.203	1.562	AN6H21A
006385765	2.328	1.688	AN6H22A
005828925	2.453	1.812	AN6H23A
005828924	2.578	1.938	AN6H24A
006385821	2.703	2.062	AN6H25A
005828922	2.953	2.312	AN6H27A
005828926	3.078	2.438	AN6H30A
006395183	3.328	2.688	AN6H32A
005828942	3.578	2.938	AN6H34A
005828943	3.703	3.062	AN6H35A
005828940	3.953	3.312	AN6H37A
000635025	4.203	3.562	AN6H41A
012759915	4.578	3.938	AN6H44A
011256188	4.703	4.062	AN6H45A
009265680	4.828	4.188	AN6H46A
005826201	4.953	4.312	AN6H47A
006385289	5.078	4.438	AN6H50A
005826202	5.203	4.562	AN6H51A
007542076	5.453	4.812	AN6H53A
002818937	5.703	5.062	AN6H55A
012759916	6.078	5.438	AN6H60A
008333072	6.453	5.812	AN6H63A
007542077	6.578	5.938	AN6H64A
008385911	7.828	7.188	AN6H76A

**Corrosion-Resistant Steel, Passivated, Drilled Shank
125,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
002759666	0.703	0.062	AN6C5
001512458	0.828	0.188	AN6C6
001512457	0.953	0.312	AN6C7
006381483	1.078	0.438	AN6C10
002759688	1.203	0.562	AN6C11
001512456	1.328	0.688	AN6C12
006392386	1.453	0.812	AN6C13
002759689	1.578	0.938	AN6C14
002823087	1.703	1.062	AN6C15
002759657	1.828	1.188	AN6C16
002822672	1.953	1.312	AN6C17
002759654	2.078	1.438	AN6C20
001800048	2.203	1.562	AN6C21
001744089	2.328	1.688	AN6C22
002822671	2.703	2.062	AN6C25
005828902	3.078	2.438	AN6C30
012367082	3.203	2.562	AN6C31

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001512392	3.328	2.688	AN6C32
003373225	3.453	2.812	AN6C33
002759653	3.828	3.188	AN6C36
005794130	4.203	3.562	AN6C41
012554600	4.953	4.312	AN6C47
010773063	5.328	4.688	AN6C52
012554601	5.703	5.062	AN6C55
008162344	6.078	5.438	AN6C60
000826699	6.578	5.938	AN6C64
011308981	7.203	6.562	AN6C71

Corrosion-Resistant Steel, Passivated, Undrilled
125,000 psi Tensile Strength

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
002075916	0.703	0.062	AN6C5A
006377696	0.828	0.188	AN6C6A
006559475	0.953	0.312	AN6C7A
005828718	1.078	0.438	AN6C10A
005828851	1.203	0.562	AN6C11A
005829588	1.453	0.812	AN6C13A
006392364	1.578	0.938	AN6C14A
005829589	1.703	1.062	AN6C15A
005790403	1.828	1.188	AN6C16A
005829009	1.953	1.312	AN6C17A
003245976	2.078	1.438	AN6C20A
002759656	2.203	1.562	AN6C21A
005829008	2.328	1.688	AN6C22A
005829007	2.453	1.812	AN6C23A
006377694	2.578	1.938	AN6C24A
005790419	2.703	2.062	AN6C25A
005826901	2.828	2.188	AN6C26A
003245977	2.953	2.312	AN6C27A
005826900	3.078	2.438	AN6C30A
005826899	3.203	2.562	AN6C31A
001801946	3.328	2.688	AN6C32A
005826898	3.453	2.812	AN6C33A
005829891	3.578	2.938	AN6C34A
005829887	3.703	3.062	AN6C35A
005829888	3.828	3.188	AN6C36A
006166259	3.953	3.312	AN6C37A
008028649	4.078	3.438	AN6C40A
000586433	4.453	3.812	AN6C43A
002759647	4.578	3.938	AN6C44A
007168459	5.078	4.438	AN6C50A
000430573	5.453	4.812	AN6C53A
002318067	5.953	5.312	AN6C57A
009682456	6.203	5.562	AN6C61A

Corrosion-Resistant Steel, Passivated, Drilled Head and Shank**125,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
002079786	0.703	0.062	AN6CH5
007256614	0.828	0.188	AN6CH6
011323348	0.953	0.312	AN6CH7
012867972	1.078	0.438	AN6CH10
005826705	1.578	0.938	AN6CH14
012759913	1.703	1.062	AN6CH15
005845503	1.953	1.312	AN6CH17
012759918	2.578	1.938	AN6CH24
012759909	2.703	2.062	AN6CH25
012759911	2.953	2.312	AN6CH27
012759919	3.078	3.812	AN6CH43

Corrosion-Resistant Steel, Passivated, Drilled Head**125,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
005844935	0.703	0.062	AN6CH5A
005844934	0.828	0.188	AN6CH6A
006392395	0.953	0.312	AN6CH7A
005826711	1.078	0.438	AN6CH10A
005826709	1.203	0.562	AN6CH11A
005826708	1.328	0.688	AN6CH12A
005826706	1.453	0.812	AN6CH13A
012850457	1.703	1.062	AN6CH15A
005826884	2.078	1.438	AN6CH20A
005829623	2.328	1.688	AN6CH22A
012759927	2.578	1.938	AN6CH24A
012759926	2.703	2.062	AN6CH25A
001452198	2.828	2.188	AN6CH26A
005844933	2.953	2.312	AN6CH27A
005844936	3.578	2.938	AN6CH34A
011559766	4.328	3.688	AN6CH42A

Aluminum Alloy, Anodized, Drilled Shank**62,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
001513257	1.328	0.688	AN6DD12
001513258	1.453	0.812	AN6DD13
001513261	1.828	1.188	AN6DD16
002696991	3.203	2.562	AN6DD31
001513271	3.578	2.938	AN6DD34

Aluminum Alloy, Anodized, Undrilled**62,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
002282891	0.703	0.062	AN6DD5A
006853750	0.828	0.188	AN6DD6A
001800142	0.953	0.312	AN6DD7A
001800141	1.078	0.438	AN6DD10A
002702483	1.203	0.562	AN6DD11A
001800140	1.328	0.688	AN6DD12A
002702484	1.453	0.812	AN6DD13A
001800139	1.578	0.938	AN6DD14A
006602356	2.453	1.812	AN6DD23A
000818286	2.828	2.188	AN6DD26A
008135098	4.203	3.562	AN6DD41A

**Aluminum Alloy, Anodized, Drilled Head and Shank
62,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
006381465	1.828	1.188	AN6DDH16

**Aluminum Alloy, Anodized, Drilled Head
62,000 psi Tensile Strength**

NIIN	FASTENER LENGTH	GRIP LENGTH	PART NUMBER
002759692	1.078	0.438	AN6DDH10A

For additional assistance please contact: AVN Testing Office PVT
Workflow AVNTestingOfficePVTWorkflow@dla.mil

[<- Table of Contents](#)

Fastener Assortments

Why re-stock your storeroom one stock number at a time, when you can order an assortment of screws, bolts, studs, nuts, and/or washers.

The below listed assortments of screws, bolts, nuts, washers, studs and threaded rods are now available for your shopping convenience. For more information, contact DLA Troop Support - Industrial Hardware at DSN: 444-7000 or Commercial: (215) 737-7000.

Screw Assortments (Steel)

NSN	UNIT of ISSUE	DESCRIPTION
5305-01-185-8786	AT	SETSCREW, HEX SOCKET, ALLOY STEEL, CUP POINT. #10 THRU 1/2" DIA. (590) SCREWS IN (11) SIZES with (115) HEX KEYS IN (7) SIZES. (705 TOTAL PIECES)
5305-01-186-7208	AT	SETSCREW, HEX SOCKET, ALLOY STEEL, CUP POINT. #6 THRU 3/8" DIAMETER SCREWS IN VARIOUS LENGTHS, COARSE & FINE THREADS. (200 TOTAL PIECES)

Screw Assortments (CRES)

NSN	UNIT of ISSUE	DESCRIPTION
5305-01-416-8563	AT	SCREWS, SELF-TAPPING NON-MACHINE THREAD, 18-8 STAINLESS STEEL, PAN HEAD, CROSS- RECESS DRIVE. 100 EA.: #6 X 3/8", 1/2", 3/4" & 1" LENGTHS; #8 X 1/2", 3/4", 1" LENGTHS; #10 X 1/2" & 3/4" LENGTHS. 50 EA.: #8 X 1-1/2" LONG; #10 X 1", 1-1/4" & 1-1/2" LENGTHS; #12 X 3/4", 1" & 1-1/2" LENGTHS. (1250 TOTAL PIECES)
5305-01-416-8576	AT	SETSCREWS, 18-8 STAINLESS STEEL, CUP POINT, HEX SOCKET DRIVE. 50 EA.: 4-40 X 1/8", 3/16" & 1/4" LENGTHS; 6-32 X 1/8", 3/16", 1/4", 5/16" & 3/8" LENGTHS; 8-32 X 1/8", 3/16", 1/4", 5/16" & 3/8" LENGTHS; 10-32 X 3/16", 1/4", 5/16", 3/8" & 1/2" LENGTHS. (900 TOTAL PIECES)
5305-01-416-8580	AT	SCREWS, MACHINE, PAN HEAD, SLOTTED, 18-8 STAINLESS STEEL. 50 EA.: 4-40 X 1/4", 3/8" & 1/2" LENGTHS; 6-32 X 1/4", 3/8", 1/2", 3/4" & 1" LENGTHS; 8-32 X 1/4", 3/8", 1/2", 3/4" & 1" LENGTHS; 10-24 X 1/2", 3/4" & 1" LENGTHS; 10-32 X 1/4", 3/8", 1/2", 3/4" & 1" LENGTHS; 1/4-20 X 1/2", 3/4" & 1" LENGTHS. (1200 TOTAL PIECES)

Screw Assortments (316 Stainless Steel)

NSN	UNIT of ISSUE	DESCRIPTION
5305-01-437-7465	AT	SOCKET HEAD SCREWS. 12 SCREW SIZES ,120 TOTAL PIECES, 10 EACH OF THE FOLLOWING: 6-32 X ½",8-32 X ½",10-32 X 3/8",1/2"5/8",3/4",1",1/4"-20 X1/2",3/4",1",1-1/2",3/8"-16 x 1".

Screw Assortments (18-8 Stainless Steel Machine Screws, Sheet Metal Screws, Nuts and Washers)

NSN	UNIT of ISSUE	DESCRIPTION
5305-01-585-9941	AT	ASSORTMENTS CONTAIN FLAT AND PAN HEAD PHILLIPS SHEET METAL AND MACHINE SCREWS, PLUS A VARIETY OF NUTS AND WASHERS. EACH INCLUDES 600 NO.6, 8 AND 10 SIZE SHEET METAL SCREWS IN LENGTHS FROM 3/8" TO 1 1/2", 150 SIZE 10-24 AND ¼-20 MACHINE SCREWS IN LENGTHS FROM 3/4" TO 1", 250 SIZE 6-32,8-32, 10-24, 1/4-20, 5/16" AND 3/8-16 NUTS AND 500 NO.6,8,10,1/4",5/16 AND 3/8" SIZE LOCK WASHERS AND FLAT WASHERS FOR A TOTAL OF 1500 PIECES. 18-8 STAINLESS STEEL ASSORTMENT COMES WITH AN ADDITIONAL 50 SIZE 10-32 MACHINE SCREW NUT FOR A TOTAL OF 1,550 PIECES.

Screw Assortments Metric (18-8 Stainless Steel)

NSN	UNIT of ISSUE	DESCRIPTION
5305-01-585-9933	AT	METRIC ASSORTMENT INCLUDES 600 M3 AND M4 PAN AND FLAT HEAD PHILLIPS SCREWS IN LENGTHS FROM 6 TO 16 MM, 600 NUTS, AND 1000 SPLIT-LOCK AND WASHERS IN SIZES M3, M4, M5, M6, M8, AND M10.